



One Machining

Maskinpark

Maskin: SMX 3100

Maskin nr: 500

Max Dreie Diameter : 600

Max Lengde: 3200

Diameter chuck: 325

Spindelboring: 101.6

Størrelse på brille: 45-310

Y-vandring: +/-150

Vandring under senter: -250

Styring: Fanuc



Maskin: Doosan 3100uly

Maskin nr: 501

Max Dreie Diameter : 420/520

Max Lengde: 3200

Diameter chuck: 325

Spindelboring: 101.6

Størrelse på brille: 30-245

Y-vandring: +/-65

Vandring under senter: -240

Styring: Fanuc



Maskin: Doosan 2600ly

Maskin nr: 502

Max Dreie Diameter : 380/480

Max Lengde: 1200

Diameter chuck: 250

Spindelboring: 76.2

Størrelse på brille: NA

Y-vandring: +/-65

Vandring under senter: -190

Styring: Fanuc



Maskin: Mas Masturn 550i

Maskin nr: 503

Max Dreie Diameter : 332

Max Lengde: 1500

Diameter chuck: 325

Spindelboring: 76.2

Størrelse på brille: NA

Y-vandring: NA

Vandring under senter: NA

Styring: Heidenhain



Maskin: SMX 3100L

Maskin nr: 504

Max Dreie Diameter : 600

Max Lengde: 2500

Diameter chuck: 400

Spindelboring: 127/101.6

Størrelse på brille: 100-410

Y-vandring: +/-150

Vandring under senter: -250

Styring: Fanuc



Maskin: Mazak Integrex 400

Maskin nr: 505

Max Dreie Diameter : 400

Max Lengde: 1500

Diameter chuck: 325

Spindelboring: 101.6

Størrelse på brille: 50-200

Y-vandring: +/-65

Vandring under senter: -25

Styring: Mazatrol 640M



Maskin: Mazak Vtc 200B

Maskin nr: 507

Max X vandring: 1120

Max Y vandring: 510

Max Z vandring: 510

B-akse: NA

C-akse: Nei

Styring: Mazatrol 640M



Maskin: Correa Norma L

Maskin nr: 508

Max X vandring: 8000

Max Y vandring: 1250

Max Z vandring: 1500

B-akse: +/-120 (2.5 grader lås)

C-akse: Ja

Styring: Heidenhain



Maskin: Mazak Smooth 400

Maskin nr: 509

Max Dreie Diameter : 600

Max Lengde: 2500

Diameter chuck: 325

Spindelboring: 101.6

Størrelse på brille: 45-320

Y-vandring: +/-125

Vandring under senter: -150

Styring: Smooth X



Maskin: DMG DMU 100

Maskin nr: 510

Max X vandring: 1200

Max Y vandring: 710

Max Z vandring: 710

B-akse: -30 +120

C-akse: Ja

Styring: Heidenhain



Maskin: Doosan 700

Maskin nr: 511

Max Dreie Diameter : 750

Max Lengde: 5050

Diameter chuck: 610

Spindelboring: 164

Størrelse på brille: 100-510

Y-vandring: +-100

Styring: Fanuc

